



75 Tacoma Circuit Canning Vale 6155  
Ph: 9455 1144  
Fax: 9455 2399  
[www.safarigroup.com.au](http://www.safarigroup.com.au)

## **INTRODUCTION**

Safecure 1000 is a Poly Vinyl Alcohol emulsion used as curing membrane on freshly poured concrete. It contains no solvents and is environmentally friendly.

- Totally Water-based
- Single pack
- Reduces plastic shrinkage
- Environmentally friendly
- Can be applied by spray, roller or brush
- Will not yellow
- Eliminates the need for curing by ponded water, damp hessian or polythene sheeting
- Seals concrete surfaces
- Equipment washable in water

## **USES**

Safecure 1000 is suitable for curing all freshly laid concrete either smooth or textured, indoors or outdoors.

## **SURFACE APPLICATION**

Apply Safecure 1000 to the concrete as soon as the bleed water has gone and the new concrete has hardened sufficiently so as not to be marked by the application process

***NOTE: ENSURE ALL EQUIPMENT IS THOROUGHLY CLEANED OUT IN WATER AS SOON AS POSSIBLE AFTER USE.***

## **TYPICAL PROPERTIES & APPLICATION DATA**

<i>Appearance:</i>	Milky White	<i>Flashpoint:</i>	N/A
<i>Finish:</i>	Semi-Gloss	<i>Solvents:</i>	18mths
<i>Coverage:</i>	5sqm/litre	<i>Shelf Life:</i>	18 mths
<i>Viscosity:</i>	22-24 sec. Ford 4 cup	<i>Tack Free:</i>	30 mins
<i>Soilds:</i>	25-27%	<i>Application Temperature:</i>	8°C-35°C
<i>Solubility:</i>	Total	<i>Application By:</i>	Brush/Roller/Spray

Refer to Material Safety Data Sheet for precautions and personal protection.

Disclaimer: Any advice, recommendation, information, assistance or service provided by Safari Building Products in relation to goods manufactured or supplied by them or their use and application is in good faith and is believed by Safari Building Products to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by Safari Building Products is provided without liability or responsibility.